

**FISHER**

# SNOWPLOW SPECIFICATIONS





# STRAIGHT BLADES

Plow Type	Blade Width	Blade Height	Blade Gauge	Angling Rams	Plowing Width	Approximate Weight*	Cutting Edge
HT Series™	7' 6"	27"	14	1½" x 8"	6' 7"	414 lb	3/8" x 6" steel; 1/2" x 6" steel 1" x 6" poly
SD Series	6' 9"	26"	14	1½" x 10"	6' 1"	472 lb	1" x 6" poly
SD Series	7' 6"	26"	14	1½" x 10"	6' 9"	487 lb	3/8" x 6" steel; 1" x 6" poly
HD Series	7' 6"	29"	12	1½" x 12"	6' 7"	630 lb	3/8" x 6"; 1/2" x 6"
HD Series	8'	29"	11	1½" x 12"	7' 1"	717 lb	1/2" x 6"
HD Series	8' 6"	29"	11	1½" x 12"	7' 6"	731 lb	1/2" x 6"
HD Series	9'	29"	11	1½" x 12"	7' 11"	745 lb	1/2" x 6"
XBLADE™	8'	31"	12	1½" x 12"	7' 1"	790 lb	1/2" x 6"
XBLADE	9'	31"	12	1½" x 12"	7' 11"	835 lb	1/2" x 6"
MC Series	9'	34"	11	2" x 16"	7' 11"	1174 lb	1/2" x 8"
MC Series	10'	34"	11	2" x 16"	8' 10"	1308 lb	1/2" x 8"

HD Series and XBLADE are available with a universal skid-steer loader mounting plate

# V-PLOWS

Plow Type	Blade Width	Blade Height at Blade End	Height at Hinge	Blade Gauge	Angling Rams	Plowing Width at Full Angle	Plowing Width at Scoop	Plowing Width at Full V	Cutting Edge	Approximate Weight*	Lift Cylinder
XtremeV™ SS	7' 6"	30¾"	29"	12	1¾" x 11"	6' 6"	6' 3"	6' 9"	3/8" x 6"; 1/2" x 6"	821 lb	1½" x 10"
XtremeV SS or PC	8' 6"	31"	29"	12	1¾" x 11"	7' 5"	7' 1"	7' 7"	3/8" x 6"; 1/2" x 6"	899 lb	1½" x 10"
XtremeV SS or PC	9' 6"	33"	31"	12	1¾" x 11"	8' 3"	7' 11"	8' 7"	1/2" x 6"	1013 lb	1½" x 10"
XV2™ SS	7' 6"	37"	31"	14	1¾" x 11"	6' 7"	6' 4"	6' 10"	3/8" x 6"; 1/2" x 6"	914 lb	1¾" x 10"
XV2 SS or PC	8' 6"	38"	31"	14	1¾" x 11"	7' 5"	7' 2"	7' 8"	3/8" x 6"; 1/2" x 6"	957 lb	1¾" x 10"
XV2 SS or PC	9' 6"	39"	31"	14	1¾" x 11"	8' 6"	8' 2"	8' 7"	1/2" x 6"	1044 lb	1¾" x 10"

SS = Stainless Steel | PC = Powder Coated Steel

# EXPANDABLE LENGTH SNOWPLOW

Plow Type	Blade Width Retracted	Blade Width Extended	Blade Width Scoop	Plowing Width at Full Angle	Blade Height	Blade/Wing Gauge	Angling Rams	Approximate Weight*	Cutting Edge (Optional)	Wing Cutting Edge Material
XLS™	8'	10'	8' 10"	7' 2" retracted; 9' expanded 7' 11" windrow mode	29"	12	1½" x 10"	985 lb	1/2" x 6" Top Punched	1½" x 9" Polyurethane

# PUSHER PLOWS

STORM BOXX™	Blade Width	Approximate Weight*	Side Plate	Snow Capacity
Skid-Steer	8'	710 lb	36" x 36"	7 yd
Skid-Steer	10'	790 lb	36" x 36"	9 yd
Backhoe	10'	1030 lb	36" x 36"	9 yd
Backhoe	12'	1150 lb	36" x 36"	11 yd
Wheel Loader	12'	1680 lb	48" x 48"	15 yd
Wheel Loader	14'	1815 lb	48" x 48"	18 yd
Wheel Loader	16'	1950 lb	48" x 48"	21 yd

\* Plus vehicle mount: approx. 60 lb (approx. 184 lb MC Series)



FISHER ENGINEERING | 50 GORDON DRIVE | ROCKLAND, MAINE 04841

FISHERPLOWS.COM |    

Fisher Engineering reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used. Fisher Engineering or vehicle manufacturer may require or recommend optional equipment for snow removal. Do not exceed vehicle ratings with a snowplow. Fisher Engineering offers a limited warranty on all snowplows and accessories. See separately printed page for this important information. The following are registered (®) and unregistered (™) trademarks of Douglas Dynamics, L.L.C.: FISHER®, HT Series™, STORM BOXX™, XBLADE™, XLS™, XtremeV™ and XV2™.